



SPECIFICATION OF HIGH VISCOSITY PARAFFINIC RPO

GENERAL DESCRIPTION OF HIGH VISCOSITY PARAFFINIC RPO

PARAFFINIC RUBBER PROCESS OIL WITH HIGH VISCOSITY INDEX IS A TRANSPARENT BROWN COLOR THIS OIL MAINLY USE IN PLASTIC PRODUCT WHICH ELASTICITY IS IMPORTANT PARAMETER. HIGH VISCOS PRARAFFINIC OIL CONTAIN 45% PARAFFINIC CARBON AND EVAPORATION IS 1% AT 150 ° C .

USES OF HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL

PARAFFINIC RUBBER PROCESS OIL WITH HIGH VISCOSITY MAINLY USE IN : RUBBER PRODUCTS SUCH AS TUBES WITH HIGH ELASTICITY, SOFT RUBBER COATING, RUBBER GASKETS, RUBBER GASKETS, SEALING RINGS , PLASTIC LAYER USED IN HOME APPLIANCES...

PACKING OF HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL

PARAFFINIC RUBBER PROCESS OIL WITH HIGH VISCOSITY IS PACKED IN NEW OR USED

180 KG DRUMS , ISO TANK , FLEXI TANKS AND BULK SHIPMENTS. EACH 20 FOOT CONTAINER TAKES 80 DRUM HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL.

GUARANTY/WARRANTY OF HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL ATDM

GUARANTY THE QUALITY OF HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL WITH ARRANGEMENT OF INTERNATIONAL INSPECTOR TO CHECK QUALITY AND



QUANTITY OF HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL DURING THE LOADING TO VESSEL AND CONTROLLING THE PRODUCTION BY QC BY BATCH TEST REPORT BEFORE SHIPPING. ATDM GUARANTY THE QUALITY TO MEET WITH ASTM.

OUR APPROVALS



HIGH VISCOSITY PARAFFINIC RPO RUBBER PROCESS OIL ANALISES:

PARRAFFINIC RUBBER PROCESS OIL	
Characteristics	TEST RESULT
Kinematic Viscosity @ 100 Deg. C, cST	15-40
AP	120
Kinematic Viscosity @ 40 Deg. C, cST	40
Flash point, Deg. C	170
PCA	3 %
Specific gravity @15 Deg C	0.97